

# Ebalta SG 700 A / PUR 5

Polyurethane  
Ebalta Kunststoff GmbH

Message:

ebalta SG 700 is a two-component-Polyurethane casting resin, which cures very fast at room temperature. The very good workability and the excellent mechanical properties makes SG 700 a material with versatile application possibilities.

ebalta SG 700 A is even more abrasion-resistant, but not so well workable by machine. Displacements, even made of wood, can be filled in.

Material should be carefully stirred up/ shaken before use.

Applications

Foundry patterns

Core boxes

fixtures

Negatives

Control castings

Prototypes

Properties

abrasion resistant

well castable

fine structure

dimensionally accurate

fast curing

versatile

General Information			
Features	Fast Cure		
	Good Abrasion Resistance		
Uses	Prototyping		
Appearance	Blue		
Processing Method	Casting		
Hardness	Nominal Value		Test Method
Shore Hardness (Shore D)	80 to 86		ISO 7619
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	4020 to 4920	MPa	ISO 178
Flexural Stress	38.0 to 48.0	MPa	ISO 178
Compressive Stress	48.0 to 58.0	MPa	ISO 604
Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength	3.7 to 5.7	kJ/m <sup>2</sup>	ISO 179
Thermal	Nominal Value	Unit	Test Method
Martens Temperature	47 to 51	°C	DIN 53458
Thermoset	Nominal Value	Unit	
Thermoset Components			
Hardener	Mix Ratio by Weight: 15		
Resin	Mix Ratio by Weight: 100		
Uncured Properties	Nominal Value	Unit	
Density (20°C)	1.70 to 1.80	g/cm <sup>3</sup>	

Viscosity (25°C)	1.5 to 2.2	Pa·s
Curing Time (20°C)	1.0 to 2.0	hr
Pot Life <sup>1</sup> (20°C)	5.0 to 7.0	min

NOTE

1. 200 g

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

