

NOVA PC 1000 BK

Polycarbonate
NOVA Polymers, Inc.

Message:

NOVA PC 1000 BK is a polycarbonate (PC) material. This product is available in North America and is processed by injection molding. The main characteristics of NOVA PC 1000 BK are: flame retardant/rated flame.

General Information			
UL File Number	E143392		
Appearance	Black		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.20	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (300°C/1.2 kg)	8.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield, 3.18 mm)	62.1	MPa	ASTM D638
Flexural Modulus (3.18 mm)	2240	MPa	ASTM D790
Flexural Strength (Yield, 3.18 mm)	93.1	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	530	J/m	ASTM D256
Flammability	Nominal Value		Test Method
Flame Rating			UL 94
3.18 mm	V-2		UL 94
6.35 mm	V-2		UL 94
Additional Information			

Moisture Content, ASTM D 4019-88: <0.04 %

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT