

# K-Flex 3340

Polyvinyl Chloride Elastomer

Technovinyl Polymers India Ltd.

## Message:

K-Flex 3340 is a Polyvinyl Chloride Elastomer (PVC Elastomer) material. It is available in Africa & Middle East.

Important attributes of K-Flex 3340 are:

Good Flexibility

Wear Resistant

Typical application of K-Flex 3340: Wire & Cable

General Information			
Features	Good Abrasion Resistance		
	Good Flexibility		
	Soft		
Uses	Wire & Cable Applications		
Appearance	Natural Color		
Physical	Nominal Value	Unit	Test Method
Density	1.18	g/cm <sup>3</sup>	ASTM D1505
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	35 to 45		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	3.92	MPa	ASTM D412
Tensile Elongation (Break)	> 400	%	ASTM D412
Thermal	Nominal Value	Unit	
Service Temperature	-25 to 100	°C	
Ozone Resistance	Excellent		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT