

# Shandong PA6 A1G6304

Polyamide 6

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong PA6 A1G6304 is a Polyamide 6 (Nylon 6) material filled with glass fiber. It is available in Asia Pacific.

Important attributes of Shandong PA6 A1G6304 are:

Flame Rated

Heat Resistant

High Strength

Wear Resistant

Typical applications include:

Appliances

Automotive

Electrical/Electronic Applications

General Information	
Filler / Reinforcement	Glass Fiber
Features	Good Wear Resistance
	High Heat Resistance
	High Strength
	Hydrolysis Resistant
Uses	Appliances
	Automotive Applications
	Electrical/Electronic Applications

Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	155	MPa
Tensile Strain (Break)	3.0	%
Flexural Modulus	8000	MPa
Flexural Stress	215	MPa
Impact	Nominal Value	Unit
Charpy Notched Impact Strength	18	kJ/m²
Charpy Unnotched Impact Strength	100	kJ/m²
Flammability	Nominal Value	Test Method
Flame Rating	HB	UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

