

Beetafin® L9047

Polyurethane (Polyester based)

BIP (Oldbury) Limited

Message:

An anionic, soft, highly flexible, light fast polyester based, aliphatic aqueous polyurethane dispersion. Thickened for ease of application.

Characteristics:

- Abrasion resistance
- Gives soft, highly extensible, tough films with a dry feel
- Gives high clarity films that do not discolour on exposure to daylight
- Normal high gloss finish may be modified by the addition of a recommended duller
- Good adhesive properties on synthetic and natural materials

Applications:

- Leather Adhesive
- Plastic Coatings & Adhesive
- Textile Adhesive
- Heat-Seal Adhesives

General Information	
Features	Aliphatic
	Good Abrasion Resistance
	Good Adhesion
	Good Flexibility
	Good Toughness
	High Clarity
	Soft
Uses	Adhesives
	Coating Applications
	Printing Ink
	Textile Applications

Physical	Nominal Value	Unit	
pH	8.0		
Solids Content	40	%	
Films	Nominal Value	Unit	
Tensile Modulus - 100%	3.50	MPa	
Tensile Strength - MD (Break)	30.0	MPa	
Tensile Elongation - MD (Break)	1000	%	
Uncured Properties	Nominal Value	Unit	Test Method
Viscosity (25°C)	5.0	Pa · s	Brookfield

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

