

Achieve™ 3854

Polypropylene Homopolymer
ExxonMobil Chemical

Message:

Exxpol using ExxonMobil Chemical™High quality homopolymer resin produced by technology, specially designed for spunbond technology. The resin has a narrow molecular weight distribution, so it shows excellent uniformity; its thinner fibers and higher tensile strength promote innovation in the application field and provide the possibility of thinning.

General Information	
Features	Pure/High Purity
	Low smoke
Uses	Spunbond nonwoven fabric
	Textile applications
	Personal care
Appearance	Natural color
Forms	Particle
Processing Method	Filament extrusion
	Fiber (spinning) extrusion

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	24	g/10 min	ASTM D1238

Legal statement
未经埃克森美孚化工书面允许,这种产品包括其产品名称,不得在任何医疗应用领域予以使用或有关潜在食品接触应用合规信息(例如:FDA,EU,HPFB),请与埃克森美孚化工客户服务代表联系.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT