

Sinvicomp SSG6066

Flexible Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinvicomp SSG6066 is a Flexible Polyvinyl Chloride material. It is available in Asia Pacific for extrusion. Primary attribute of Sinvicomp SSG6066: Good Flexibility.

Typical application of Sinvicomp SSG6066: Wire & Cable

General Information			
Features	Good Flexibility		
Uses	Cable Jacketing		
	Wire & Cable Applications		
Forms	Granules		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.47	g/cm ³	ASTM D792
Congo Red (190°C)	1.0	hr	BS 2782
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	79		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	15.0	MPa	IEC 811-1-1
Tensile Elongation (Break)	300	%	IEC 811-1-1

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT