

Prime Polypro™ F327BV

Polypropylene Random Copolymer

Prime Polymer Co., Ltd.

Message:

Prime Polypro™ F327BV is a Polypropylene Random Copolymer (PP Random Copolymer) product. It can be processed by cast film or film extrusion and is available in Asia Pacific, Europe, or North America. Typical application: Film. Primary characteristic: good sealability.

General Information	
Features	Low Temperature Heat Sealability
Uses	Cast Film
	Film
Processing Method	Cast Film
	Film Extrusion

Physical	Nominal Value	Unit	Test Method
Density	0.910	g/cm³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	7.0	g/10 min	ISO 1133
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness	85		ISO 2039-2
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	850	MPa	ISO 527-2
Tensile Stress (Yield)	23.0	MPa	ISO 527-2
Tensile Strain (Break)	< 200	%	ISO 527-2
Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength (23°C)	12	kJ/m²	ISO 179
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed)	80.0	°C	ISO 75-2/B

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT