RapidVac[™] VA-1805

Polyurethane Thermoset Elastomer

Innovative Polymers, Inc.

Message:

VA-1805 is a 80 shore A polyure than elastomer formulated for hand-batch processing, vacuum assisted processing or meter mix dispensed. Excellent physical properties can be obtained with a room temperature cure without the utilization of mercury. MOCA, or TDI. VA-1805 has excellent green strength for quick demold times.

General Information				
Features	Good Green Strength			
RoHS Compliance	RoHS Compliant			
Appearance	Black			
Processing Method	Vacuum Casting			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity				
Cured	1.12	g/cm³		
Hardener	1.14	g/cm³		
Base Resin	1.21	g/cm³		
Molding Shrinkage - Flow	0.20 to 0.50	%	ASTM D2566	
Thermoset	Nominal Value	Unit	Test Method	
Thermoset Components				
	Mix Ratio by Volume: 100	Mix Ratio by Volume: 100		
Handanan				
Hardener	Mix Ratio by Weight: 100			

Mix Ratio by Weight: 80

Mix Ratio by Volume: 72		
30 to 60	min	
Nominal Value	Unit	Test Method
0.55	Pa·s	
1.8	Pa·s	
4.5	Pa·s	
25	hr	
4.0 to 6.0	min	
Nominal Value	Unit	Test Method
70 to 80		ASTM D2240
6.21	MPa	ASTM D638
	30 to 60 Nominal Value 0.55 1.8 4.5 25 4.0 to 6.0 Nominal Value 70 to 80	30 to 60minNominal ValueUnit0.55Pa·s1.8Pa·s4.5Pa·s25hr4.0 to 6.0minNominal ValueUnit70 to 80

Tensile Elongation at Break	100	%	ASTM D638	
Tear Strength	14.0	kN/m	ASTM D624	
NOTE				
1.	Hardener			
2.	Mixed			
3.	Resin			
4.	24 hours at 77°F + 1 hour at 150°F			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

