

Taitacell EPS 321Ss

Expanded Polystyrene

Taita Chemical Company, Ltd.

Message:

Taitacell EPS 321Ss is an Expanded Polystyrene material. It is available in Asia Pacific or North America. Primary attribute of Taitacell EPS 321Ss: Flame Retardant.

Typical applications include:

Construction Applications

Packaging

Wire & Cable

General Information	
Additive	Flame Retardant
Features	Flame Retardant
Uses	Construction Applications
	Insulation
	Packaging

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.0150 to 0.0300	g/cm ³	ASTM D792
Water Content	< 0.50	%	
Bead Size ¹	700.0 to 900.0	μm	

Chemical Resistance	
Acid	Good
Alkali	Good
Solvent	Poor
Expandability	65.0 to 80.0

Mechanical	Nominal Value	Unit	Test Method
Flexural Strength	> 0.245	MPa	ASTM D790
Compressive Strength (10% Strain)	> 0.0785	MPa	ASTM D695

Thermal	Nominal Value	Unit	Test Method
Thermal Conductivity	0.031 to 0.042	W/m/K	ASTM C177

NOTE	
1.	95% min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

