

NHU-PPA N200

Polyphthalamide

Zhejiang NHU Comp. Ltd.

Message:

NHU-PPA Polymer is a polyamide-class high temperature nylon resin with high distortion temperature, excellent tenacity and frictional resistance. Featuring good melt flow rate, PPA resin boasts excellent injection molding processibility, acid, alkali and general chemical resistance as well as outstanding mechanical strength.

General Information			
Features	Excellent Processability High strength Good liquidity Good chemical resistance alkali resistance Heat resistance, high acid resistance		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Viscosity Number	90.0	cm ³ /g	ISO 307
Moisture Content ¹		%	
Ash Content (750°C)	0.25	%	ISO 3451
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	123	°C	ISO 11357-2
Melting Temperature	315	°C	ISO 11357-3
NOTE			
1.	150°C, 0.3 hour		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

