

Moplen HP525N

Polypropylene Homopolymer

LyondellBasell Industries

Message:

Moplen HP525N is a polypropylene homopolymer. With its high clarity, high slip and anti-blocking properties, it is especially suitable for water-quenched blown film (iPP). Potential end use applications include packaging for hosiery, shirts, other textiles, and food.

General Information	
Additive	Antiblock High Slip
Features	Antiblocking Food Contact Acceptable Good Processability Good Stiffness High Clarity High Slip Homopolymer
Uses	Film Food Packaging
Forms	Pellets
Processing Method	Blown Film Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.900	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	11	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	34.0	MPa	ASTM D638
Tensile Elongation (Yield)	10	%	ASTM D638
Flexural Modulus	1500	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	26	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method

Deflection Temperature Under Load (0.45 MPa, Unannealed)	100	°C	ASTM D648
--	-----	----	-----------

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

