

# HANWHA KH-31S

Polyvinyl Chloride

Hanwha Chemical

## Message:

Feature: Low viscosity and low deterioration. High thermal stability with form cell. Soft texture after forming

Use: Casting leather and form products (wall paper and mats)

General Information			
Features	Low viscosity		
	Thermal stability, good		
	Soft		
Uses	Synthetic Leather		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.25 - 0.33	g/cm <sup>3</sup>	ASTM D1895
Volatile Matter		%	ASTM D3030
Particle size-100Mesh(150μm) Sieve Pass%	100	%	Internal method
Brokfield viscosity-cps/6rpm			ASTM D1824
degree of polymerization			
DP	1550 - 1650		JIS K6720-2
K-Value	75.0		DIN 53726
Additional Information	Nominal Value	Test Method	
Liquidity: Dilatant			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

