Sinpolene MBB3132

Low Density Polyethylene

Teknor Apex Asia Pacific PTE. LTD.

Message:

SINPOLENE MBB3132 is a masterbatch based on a furnace carbon black dispersed in polyethylene. It is designed specifically for use in general film, mulch film, extrusion of sheet and molding of polyethylene.

SINPOLENE MBB 3132 is delivered as free flowing pellets for processing convenience. The product should be stored in dry place.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * Higher jetness
- * Minimal wear effect on processing equipment

General Information	
Uses	Films
	Sheet
Forms	Particle
Processing Method	Blow film
	Sheet extrusion moldina

Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.14	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (190°C/10.0				
kg)	< 15	g/10 min	ASTM D1238	
Carbon Black Content	40	%	ASTM D1603	
Moisture Content		%	ASTM D3030	
Additional Information				

High PerformanceMBB3132 is compliant to food contact

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

