

Devcon Floor Patch™

Epoxy; Epoxide

Devcon

Message:

All-purpose concrete patching compound that bonds to concrete, brick, masonry, metal, or wood surfaces.

Intended Use:

Ideal for patching concrete, brick, masonry, floors, or retaining walls where the concrete has spalled. The material will also bond to wood and metal. Can be used to anchor bolts in concrete.

Product Features:

Easy to mix and apply

Trowelable to 1/4" or more

High compressive strength

Resistant to water, oils, solvents, and alkalis

General Information			
Features	Solvent resistance		
	Adhesiveness		
	Good compressive strength		
	alkali resistance		
	Oil resistance		
Uses	Floor maintenance/repair		
	Repair Materials		
Appearance	Light gray		
Physical	Nominal Value	Unit	Test Method
Solid content-by Volume	100	%	
Temperature Resistance			
Dry	121	°C	
Wet	49	°C	
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	85		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Compressive Strength	55.2	MPa	ASTM D695
Thermoset	Nominal Value	Unit	
Thermoset Components			
Resin	Mixing ratio by weight: 5.5		
Hardening method	Mixing ratio by weight: 1.0		
Pot Life (24°C)	45	min	
Additional Information	Nominal Value	Unit	
Cured 7 days @ 75°F			
Uncured Properties	Nominal Value	Unit	
Curing Time (24°C)	16	hr	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

