

PETILEN YY S 00356

High Density Polyethylene
PETKIM Petrokimya Holding A.S.

Message:
PETILEN YY S 00356 is a High Density Polyethylene product. It can be processed by blow molding and is available in Asia Pacific, Europe, or North America. Typical application: Containers.

General Information			
Uses	Blow Molding Applications		
	Containers		
	Drums		
Forms	Pellets		
Processing Method	Blow Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.950 to 0.955	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.020 to 0.060	g/10 min	ASTM D1238
Environmental Stress-Cracking Resistance (F50)	> 600	hr	ASTM D1693
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	24.0	MPa	
Break	36.0	MPa	
Tensile Elongation (Break)	830	%	ASTM D638
Flexural Modulus	820	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	660	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT