

POLYFLON™ D-6A

Polytetrafluoroethylene

DAIKIN AMERICA, INC.

Message:

Daikin-Polyflon PTFE D-6A is a homopolymer polytetrafluoroethylene aqueous dispersion. D-6A has been designed for general use in yarn coating, packing impregnation and glass fabric coating applications where increased build is desired. D-6A contains a more environmentally friendly surfactant that leaves fewer residues in the substrate than traditional surfactants.

General Information			
Features	Homopolymer		
Uses	Coating application		
Appearance	White		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.50	g/cm ³	ASTM D792
Additional Information			

Specific Gravity, hydrometer, 25°C: 1.50-1.53Viscosity, Daikin test method, 25°C: 15-30pH @ 25°C, ASTM D4441: 9-11Solids Content, ASTM D4441: 59-61%Surfactant Content, ASTM D4441: 6.2-7.4%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

