

Jampilen BA238G3

Polypropylene Copolymer
Jam Polypropylene Company

Message:

Jampilen BA238G3 is a non-filled polypropylene copolymer for injection molding with very high impact strength. The product has good U.V. resistance designed for outdoor applications. This grade is specially used for bumpers.

General Information			
Features	Copolymer		
	Good UV Resistance		
	High Impact Resistance		
Uses	Automotive Bumper		
	Outdoor Applications		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	12	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	20.0	MPa	ASTM D638
Tensile Elongation (Yield)	6.0	%	ASTM D638
Flexural Modulus	1000	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-20°C	100	J/m	
23°C	500	J/m	
Thermal	Nominal Value	Unit	Test Method
Accelerated Oven Ageing (150°C)	360	hr	ASTM D3012

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT