

Capa™ 6800

Polycaprolactone

Perstorp Holding AB

Message:

Description

Capa™ 6800 is a high molecular weight linear polyester derived from caprolactone monomer.

Supplied in granular form, approx. 3 mm pellets.

Applications

Capa™ 6800 is used in a variety of adhesive applications.

Compatible with a wide range of common thermoplastics and soluble in several common solvents.

General Information		
Features	Biodegradable	
	High Molecular Weight	
Uses	Adhesives	
Forms	Pellets	
Physical	Nominal Value	Unit
Melt Mass-Flow Rate (MFR) ¹ (160°C/5.0 kg)	2.0 to 4.0	g/10 min
Color - Hazen	< 75	
Molecular Weight	80000	
Solubility	9.34 to 9.43	(cal/cm ³) ^{0.5}
Water Content	< 0.35	%
Pellet Size	3.00	mm
Mechanical	Nominal Value	Unit
Tensile Strain (Break)	800	%
Thermal	Nominal Value	Unit
Melting Temperature	58.0 to 60.0	°C
NOTE		
1.	1" PVC die	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT