

HI-ZEX™ 530E

High Density Polyethylene

Prime Polymer Co., Ltd.

Message:

HI-ZEX™ 530E is a High Density Polyethylene product. It can be processed by extrusion and is available in Asia Pacific, Europe, or North America. Applications of HI-ZEX™ 530E include electrical/electronic applications, industrial applications and plumbing/piping/potable water. Primary characteristic: good stiffness.

General Information			
Features	Good Stiffness		
Uses	Conduit		
	Industrial Applications		
	Piping		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.960	g/cm ³	ISO 1183
Environmental Stress-Cracking Resistance	380	hr	ASTM D1693
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D, Compression Molded)	66		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus (Compression Molded)	1400	MPa	ISO 527-2
Tensile Stress (Yield, Compression Molded)	31.0	MPa	ISO 527-2
Tensile Strain (Break, Compression Molded)	< 100	%	ISO 527-2
Flexural Modulus (Compression Molded)	1500	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength	10	kJ/m ²	ISO 179
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	122	°C	ISO 306
Melting Temperature	134	°C	ISO 11357-3

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

