SABIC® Polyester SF 312

Polyethylene Terephthalate

Saudi Basic Industries Corporation (SABIC)

Message:

Polyester short staple fiber for Ring and open end spinning Polyester Short Staple Fibers (bright and round) 1.5 dtex (1.4 den) x 38mm

| General Information | |
|------------------------|----------------------------|
| Uses | staple fiber |
| | Textile applications |
| | Mixing |
| | |
| Forms | bag |
| Processing Method | Fiber (spinning) extrusion |
| Additional Information | |

Titre Decitex setting, SABIC 0010: 1.55 dtexTitre Denier setting, SABIC 0010: 1.40 denTitre deviation: ± 3%Staple length, SABIC 0006: 38 ± 2 mmNo. of crimps/cm, SABIC 0014, Double crimps: 5.0 - 7.0Hot air shrinkage, SABIC 0017, 190 °C, 20 min: 5.5 - 9.5%Moisture, SABIC 0031: < 0.4% w/wOil pick up, SABIC 0054: 0.11-0.17% w/wTenacity at break, SABIC 0012, Decitex setting: 58 - 63 cN/texTenacity at break, SABIC 0012, Denier setting: 6.6 - 7.2 gm/denElongation at break, SABIC 0012: 18 - 24%Luster: Bright

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



Page 1