

Taitacell EPS 361F

Expanded Polystyrene

Taita Chemical Company, Ltd.

Message:

Taitacell EPS 361F is an Expanded Polystyrene material. It is available in Asia Pacific or North America.

Typical application of Taitacell EPS 361F: Packaging

General Information			
Uses		Food Packaging Packaging	
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.0170 to 0.0350	g/cm ³	ASTM D792
Styrene Content	< 1000	ppm	
Water Content	< 0.50	%	
Bead Size ¹	500.0 to 850.0	μm	
Chemical Resistance			
Acid	Good		
Alkali	Good		
Solvent	Poor		
Expandability	55.0 to 70.0		
Mechanical	Nominal Value	Unit	Test Method
Flexural Strength	> 0.294	MPa	ASTM D790
Compressive Strength (10% Strain)	> 0.0785	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Thermal Conductivity	0.031 to 0.042	W/m/K	ASTM C177
NOTE			

1. 95% min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT