

PETILEN F5-21T

Low Density Polyethylene

PETKIM Petrokimya Holding A.S.

Message:

PETILEN F5-21T is a Low Density Polyethylene product. It is available in Asia Pacific, Europe, or North America.

General Information			
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.919 to 0.923	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	4.1 to 5.4	g/10 min	ASTM D1238
Ash Content ¹	0.1	wt%	Internal Method
Film Quality ²	A		Internal Method
Optical	Nominal Value	Unit	Test Method
Gloss	70		ASTM D2457
Haze	6.9	%	ASTM D1003
NOTE			
1.	ALKATHENE 509		
2.	ALKATHENE 36		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT