

Sinpolene MBN4032

Low Density Polyethylene

Teknor Apex Asia Pacific PTE. LTD.

Message:

SINPOLENE MBN 4032 is a polyethylene-based UV masterbatch suitable for stabilization of thin section articles, especially for fibre and tapes. SINPOLENE MBN4032 exhibits very good heat stability and compatibility.

General Information			
Additive	Ultraviolet stabilizer (15%)		
Features	UV absorption		
Uses	Strap		
	Fiber		
Forms	Particle		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.915	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	> 20	g/10 min	ASTM D1238
Moisture Content		%	ASTM D3030
Additional Information			

1% to 4% of masterbatch is recommended depending on application and thickness of productMaximum recommended storage time under suitable conditions (cool and dry): 5 years.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

