EVERLON® TS-85

Styrene Ethylene Butylene Styrene Block Copolymer Ever Polymer Co., Ltd.

Message:

Generally grade: Base on SEBS. suitable for insert molding, excellent bonding PP.

All kinds of hardness are prepared very well, excellent weatherability, stability of UV and the physical mechanical property.

General Information			
Features	Bondability		
	Good Weather Resistance		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.998	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	85		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength	8.34	MPa	ASTM D412
Tensile Elongation (Break)	500	%	ASTM D412
Tear Strength	49.0	kN/m	ASTM D624
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-40.0	°C	ASTM D746

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

