Trademark PE LD0720C

Low Density Polyethylene

Trademark Plastics Corporation

Message:

Trademark PE LD0720C is a Low Density Polyethylene product. It is available in North America. Applications of Trademark PE LD0720C include bags/liners, film, food contact applications and wrap.

Characteristics include:

Antiblock

Food Contact Acceptable

Good Processability

Good Toughness

General Information				
Additive	Antiblock			
Features	Additive Free			
	Antiblocking			
	Food Contact Acceptable			
	Good Drawdown			
	Good Processability			
	Good Toughness			
Uses	Film			
	Heavy-duty Bags			
	Liners			
	Shrink Wrap			
Agency Ratings	FDA 21 CFR 177.1520(c) 2.1			
Physical	Nominal Value	Unit	Test Method	
Density	0.920	g/cm³	ASTM D1505	
Melt Mass-Flow Rate (MFR) (190°C/2.16				
kg)	0.70	g/10 min	ASTM D1238	
Films	Nominal Value	Unit	Test Method	
Film Thickness - Tested	51	μm		
Secant Modulus			ASTM D882	
1% Secant, MD : 51 μm, Blown Film	172	МРа		
1% Secant, TD : 51 μm, Blown Film	217	MPa		
Tensile Strength			ASTM D882	
MD : Break, 51 μm,Blown Film	23.4	MPa		
TD : Break, 51 µm,Blown Film	16.5	MPa		
Tensile Elongation			ASTM D882	
MD : Break, 51 μm,Blown Film	170	%		
TD : Break, 51 µm,Blown Film	490	%		

130	g	ASTM D1709
		ASTM D1922
290	g	
180	g	
Nominal Value	Unit	Test Method
11	%	ASTM D1003
Nominal Value	Unit	
	290 180 Nominal Value	290 g 180 g Nominal Value Unit

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

