

Evermore PUR UP-9430NL

Polyurethane (Polyester based)

Evermore Chemical Industry Co., Ltd.

Message:

Evermore PUR UP-9430NL is a Polyurethane (Polyester based) (PUR-Ester) product. It is available in Asia Pacific. Typical application: Coating Applications.

Characteristics include:

Good Flexibility

Moisture Resistant

General Information			
Features	Aliphatic		
	Good Flexibility		
	Moisture Resistant		
Uses	Coating Applications		
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	2.65 to 3.63	MPa	ASTM D412
Tensile Strength (Yield)	> 29.4	MPa	ASTM D412
Tensile Elongation (Break)	> 500	%	ASTM D412
Fill Analysis	Nominal Value	Unit	Test Method
Melt Viscosity (25.0°C)	< 0.500	Pa · s	ASTM D3835
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	30 to 34	%	
Solvents	H2O, ACETONE		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT