

ADMER™ NE062E

Polyethylene
Mitsui Chemicals Europe GmbH

Message:

ADMER® NE062E is an maleic anhydride grafted, PE-based adhesive designed for multilayer plastic pipes composed of PE, PEX, PE-RT and Aluminum. It offers advanced adhesion durability, high heat resistance and good processability.

General Information			
Features	Durable		
	Food Contact Acceptable		
	Good Adhesion		
	Good Processability		
	High Heat Resistance		
Uses	Adhesives		
	Food Service Applications		
	Non-specific Food Applications		
	Piping		
Agency Ratings	FDA 21 CFR 175.105		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.910	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	4.5	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	46		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	8.00	MPa	
Break	19.0	MPa	
Tensile Elongation (Break)	> 500	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact (Area)	No Break		ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	83.0	°C	ASTM D1525
Peak Melting Temperature	122	°C	ASTM D3418
Oxidation Induction Time (210°C)	65	min	ISO 11357-6
Extrusion	Nominal Value	Unit	
Cylinder Zone 1 Temp.	180 to 200	°C	
Cylinder Zone 2 Temp.	180 to 200	°C	

Cylinder Zone 3 Temp.	200 to 230	°C
Cylinder Zone 4 Temp.	200 to 230	°C
Melt Temperature	200 to 230	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

