

EPAMOULD 295A1040

Thermoplastic Polyurethane Elastomer (Polyester)

Epaflex Polyurethanes S.R.L.

Message:

EPAMOULD 295A1040 is a thermoplastic polyurethane elastomer (polyester)(TPU-polyester) product. It can be processed by extrusion or injection molding and is available in Europe.
Features include:
High Flexibility
high strength
accessible food

| General Information | | |
|------------------------------|-----------------------------|-------------------|
| Additive | Beeswax | |
| Features | High Flexibility | |
| | High strength | |
| | Hydrolysis resistance | |
| | Compliance of Food Exposure | |
| Appearance | Clear/transparent | |
| Processing Method | Extrusion | |
| | Injection molding | |
| Physical | Nominal Value | Unit |
| Density | 1.19 | g/cm ³ |
| Hardness | Nominal Value | Unit |
| Durometer Hardness (Shore A) | 95 | |
| Mechanical | Nominal Value | Unit |
| Abrasion Loss | 35.0 | mm ³ |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT