Caltex PP MB71

Polypropylene

GS Caltex

Message:

Caltex PP MB71 is a Polypropylene material. It is available in Asia Pacific. Important attributes of Caltex PP MB71 are: High Gloss High Stiffness Typical applications include: Appliances Electrical/Electronic Applications

General Information			
Features	High Gloss		
	High Stiffness		
Uses	Appliance Components		
	Appliances		
	Electrical Parts		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.980	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	45	g/10 min	ASTM D1238
Molding Shrinkage			ASTM D955
Flow	1.5	%	
Across Flow	1.4	%	
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	90		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	28.4	MPa	ASTM D638
Tensile Elongation (Break)	290	%	ASTM D638
Flexural Modulus	1770	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	83	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45			
MPa, Unannealed)	125	°C	ASTM D648
Vicat Softening Temperature	150	°C	ASTM D1525
Optical	Nominal Value		Test Method
Gardner Gloss	80		ASTM D523
Injection	Nominal Value	Unit	

Processing	(Melt)	Temp
------------	--------	------

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

