Geon™ Vinyl Flexible 90048

Flexible Polyvinyl Chloride

PolyOne Corporation

Message:

Geon™Vinyl Flexible 90048 is a flexible polyvinyl chloride product. It can be processed by co-extrusion or extrusion and is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. Geon™Vinyl Flexible 90048 applications include the automotive industry and outdoor applications. The main characteristics are: high gloss.

General Information			
Features	Highlight		
Uses	Application in Automobile Field		
	Car exterior decoration		
	Outdoor application		
Appearance	Clear/transparent		
Forms	Particle		
Processing Method	Co-extrusion molding		
	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.25	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D, 15 sec)	37		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Break)	22.0	MPa	ASTM D638
Tensile Elongation ² (Break)	290	%	ASTM D638
Tear Resistance ³	70.0	kN/m	ASTM D1004
Low Temperature Flexibility ⁴ (-29°C, 508.0			
μm)	Pass		
Volatile Loss ⁵ (105°C, 1.91 mm)	0.40	%	ASTM D1203B
Antifungal	Pass		ASTM G21
Xenon Weatherometer ⁶	Pass		SAE J1960
Additional Information	Nominal Value	Unit	Test Method
注释:汽车OEM认证			
NOTE			
1.	Type 4, 510mm/min		
2.	Type 4, 510mm/min		
3.	Mold C,2 inches/min		
4.	4 hours, 12mm		
5.	Method A		

6.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

