Nipol® 1571H

Latex

Zeon Corporation

Message:

Latex of acrylonitrile butadiene copolymer (NBR latex)

Characteristics

High nitrile. Standard modified carboxyl. Good infiltration, adhesive strength and low discoloration with paper, fabrics, and wood. Good oil proof properties and solvent resistance.

Applications

Paper packing, polishing fabrics, gaskets, and battery separators.

General Information			
Features	Copolymer		
	Good Adhesion		
	Oil Resistant		
	Solvent Resistant		
Uses	Fabrics		
	Gaskets		
Physical	Nominal Value	Unit	
Solution Viscosity	15	mPa∙s	
Average Particle Size	120	nm	
рН	8.3		
Surface Tension	28	mN/m	
Total Solids	40	%	
Thermal	Nominal Value	Unit	Test Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

°C

DSC

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

-8.00

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

Glass Transition Temperature

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

