

Plexar® PX6008X01

Polypropylene
LyondellBasell Industries

Message:

Plexar tie-layers are chemically modified resins used to bond unlike materials, primarily in packaging and industrial applications. Common adherents include polyethylene resins and copolymers, EVA, EMA, polypropylene, polyamide (nylon), ethylene vinyl alcohol copolymers (EVOH), ionomer and other sealants, polyethylene terephthalate (PET) resins and copolymers, styrenic polymers, metal, and paperboard. Product grades primarily used for blown and cast films, sheet and thermoforming, blow molding, extrusion coating and lamination, tubing, pipe, and other specialty applications are available in pellet form. Contact your Plexar sales and/or Equistar technical service representative for more information and specific recommendations for your application(s).

General Information	
Uses	Blown Film
	Laminate
	Piping system
	Pipe fittings
	cast film
	Sheet
	Bottle
Forms	Particle
Processing Method	Blow film
	Blow molding
	Pipeline extrusion molding
	Extrusion blow molding
	Extrusion coating
	cast film
	Sheet extrusion molding
	Thermoforming

Physical	Nominal Value	Unit
Density (23°C)	0.892	g/cm ³
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	6.5	g/10 min
Thermal	Nominal Value	Unit
Vicat Softening Temperature	140	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

