

KRATON® D1186 B

Styrene Butadiene Styrene Block Copolymer

Kraton Polymers LLC

Message:

Kraton D1186 B is a clear, branched triblock copolymer based on styrene and butadiene with a polystyrene content of 30%. It is supplied from South America in the physical form identified below.

Kraton D1186 BT - supplied as a porous pellet dusted with talc

Kraton D1186 B polymer is used as a modifier of bitumen in roofing felt compounds, roads and pipe coating. It may also be suitable for use in formulating adhesives, sealants and coatings and in the modification of polymers.

General Information			
Additive	Antioxidant		
Features	Antioxidant		
	Block Copolymer		
Uses	Adhesives		
	Coating Applications		
	Pipe Coatings		
	Plastics Modification		
	Sealants		
Appearance	Clear/Transparent		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.940	g/cm ³	ISO 2781
Apparent Density	0.40	g/cm ³	ASTM D1895B
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	< 1.0	g/10 min	ISO 1133
Solution Viscosity ¹	1000 to 1400	mPa · s	Internal Method
Bound Styrene	29.0 to 31.0	%	Internal Method
Antioxidant Additive	>0.25	%	Internal Method
Ash Content - BT	< 0.50	%	ISO 247
Total Extractables	< 1.4	%	Internal Method
Volatile Matter	< 0.30	%	Internal Method
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A, 10 sec, Compression Molded)	74		ISO 868
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (300% Strain)	3.00	MPa	ISO 37
Tensile Stress (Yield)	24.0	MPa	ISO 37
Tensile Elongation (Break)	800	%	ISO 37
NOTE			
1.	15%w toluene solution at 25°C		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

