

HIPOLEN P® TM 21

Polypropylene Homopolymer

HIPOL A.D.

Message:

HIPOLEN P® TM 21 is a Polypropylene Homopolymer (PP Homopolymer) product. It is available in Africa & Middle East or Europe. Applications of HIPOLEN P® TM 21 include fabrics/fibers and outdoor applications. Primary characteristic: good uv resistance.

General Information			
Features	Good UV Resistance		
	Narrow Molecular Weight Distribution		
Uses	BCF Multifilaments		
	Fabrics		
	Fibers		
	Outdoor Applications		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.900	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/1.2 kg)	30	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Elongation (Break)	30	%	ASTM D638
Flexural Modulus	1100	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	30	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

