

# K-vinyl 70 Deg C Rating Sheathing (Dry)

Polyvinyl Chloride

Technovinyl Polymers India Ltd.

## Message:

K-vinyl 70 Deg C Rating Sheathing (Dry) is a Polyvinyl Chloride material. It is available in Africa & Middle East. Primary attribute of K-vinyl 70 Deg C Rating Sheathing (Dry): RoHS Compliant.

Typical application of K-vinyl 70 Deg C Rating Sheathing (Dry): Wire & Cable

General Information			
Features	Low (to None) Lead Content		
Uses	Wire & Cable Applications		
RoHS Compliance	RoHS Compliant		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.47	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	85		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	13.3	MPa	ASTM D638
Tensile Elongation (Break)	230	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-18.0	°C	ASTM D746

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT