

TYMAX® GT4157

Linear Low Density Polyethylene

Westlake Chemical Corporation

Message:

Westlake GT4157 is an anhydride modified linear low density polyethylene designed for blown film extrusion that contains no slip and no antiblock additives. This resin is designed to function as a coextruded tie layer in multilayer film applications. Westlake GT4157 is designed to tie LLDPE to resins that typically have poor bonding characteristics such as polyamide and EVOH.

General Information			
Uses	Film		
	Multilayer Film		
	Packaging		
	Tie-Layer		
Processing Method		Blown Film	
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm ³	ASTM D4883
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.0	g/10 min	ASTM D1238
Thermal	Nominal Value	Unit	Test Method
Peak Melting Temperature	122	°C	ASTM D3418
Peak Crystallization Temperature (DSC)	103	°C	ASTM D3418

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT