

Fainplast PVC PG 58/K1-UV

Polyvinyl Chloride + NBR

Fainplast Compounds S.r.l

Message:

Fainplast PVC PG 58/K1-UV is a Polyvinyl Chloride + NBR (PVC+NBR) product. It can be processed by extrusion and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Engineering/Industrial Parts. Primary characteristic: good uv resistance.

| General Information | | | |
|--------------------------|--------------------|-------------------|-------------|
| Features | Good UV Resistance | | |
| Uses | Gaskets | | |
| Processing Method | Extrusion | | |
| Physical | Nominal Value | Unit | Test Method |
| Density | 1.21 | g/cm ³ | ISO 1183 |
| Hardness | Nominal Value | Unit | Test Method |
| Shore Hardness (Shore A) | 58 | | ISO 868 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Stress (Break) | > 10.0 | MPa | ISO 527-2 |
| Tensile Strain (Break) | > 300 | % | ISO 527-2 |
| Thermal | Nominal Value | Unit | Test Method |
| Cold Flexibility | -40 | °C | ISO 458/2 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

