

Braskem PP DR155.02

Polypropylene Random Copolymer

Braskem Europe GmbH

Message:

DR155.02 Performance Random Copolymer has been specifically developed for film extrusion applications. The polymer combines features like good processing and excellent mechanical property balance.

Applications:

Specialty film e.g. multilayer component

Shrink film

Process:

Blown film

General Information	
Features	Workability, good Random copolymer
Uses	Blown Film Films Multilayer film Shrinkable film
Agency Ratings	FDA 21 CFR 177.1520(c) 3.1a Europe 10/1/2011 12:00:00 AM
Processing Method	Film extrusion Blow film

Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	2.0	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus (Injection Molded)	900	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C, Injection Molded)	18	kJ/m ²	ISO 179/1eA

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

