

CONAP® AD-6408

Polyurethane
Cytec Industries Inc.

Message:

CONAP AD-6408 is a two-component polyurethane system formulated for filter sealant applications.
CONAP AD-6408 exhibits superior penetration of filter media substrates and is based on components that are FDA and NSF approvable.

General Information		
Uses	Sealants	
Agency Ratings	FDA Food Contact, Unspecified Rating	
	NSF Unspecified Rating	
Appearance	Amber	
Physical	Nominal Value	Unit
Specific Gravity		
-- 1	1.01	g/cm ³
-- 2	1.13	g/cm ³
Hardness	Nominal Value	Unit
Durometer Hardness (Shore D)	40	
Elastomers	Nominal Value	Unit
Tensile Stress (100% Strain)	17.0	MPa
Tensile Strength	19.3	MPa
Tensile Elongation (Break)	110	%
Tear Strength	33.1	kN/m
Thermoset	Nominal Value	Unit
Thermoset Components		
Hardener	Mix Ratio by Weight: 90	
Resin	Mix Ratio by Weight: 100	
Thermoset Mix Viscosity (25°C)	10000	cP
NOTE		
1.	Hardener	
2.	Resin	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

