# McCann PP M20CHPP10

### Polypropylene Homopolymer

#### McCann Plastics Inc.

#### Message:

McCann PP M20CHPP10 is a Polypropylene Homopolymer (PP Homopolymer) product filled with 20% calcium carbonate. It is available in North America. Applications of McCann PP M20CHPP10 include appliances, furniture and household applications. Characteristics include: Flame Rated Good Stiffness Good UV Resistance High Gloss Homopolymer

General Information					
Filler / Reinforcement	Calcium Carbonate,20% Filler by	Calcium Carbonate,20% Filler by Weight			
Additive	UV Stabilizer	UV Stabilizer			
Features	Good Flow				
	Good Impact Resistance				
	Good Stiffness				
	Good UV Resistance				
	High Gloss				
	Homopolymer				
Uses	Appliances				
	Furniture				
	General Purpose				
	Lawn and Garden Equipment				
Appearance	Black				
	Colors Available				
	Natural Color				
Forms	Pellets				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.04	g/cm³	ASTM D792		
Melt Mass-Flow Rate (MFR)	10	g/10 min	ASTM D1238		
Molding Shrinkage - Flow	1.2 to 1.6	%	ASTM D955		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	98		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength	30.3	MPa	ASTM D638		
Tensile Elongation (Yield)	80	%	ASTM D638		

Flexural Modulus - Tangent	2070	MPa	ASTM D790
Flexural Strength	53.8	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	43	J/m	ASTM D256
Gardner Impact	12.4	J	ASTM D3029
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load			ASTM D648
0.45 MPa, Unannealed	110	°C	
1.8 MPa, Unannealed	62.2	°C	
Flammability	Nominal Value		Test Method
Flame Rating	НВ		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

