# NEFTEKHIM PP 1502H (S30S)

## Polypropylene Homopolymer

Nizhnekamskneftekhim Inc.

#### Message:

Product obtained by polymerization of propylene in presence of complex organic metal catalysts.

It incorporates increased long-term thermal stability, thermaloxidative degradation resistance when PP is produced, processed and PP-made articles are exploited

Application: packaging, band, film thread, technical parts, extrusion, hot shaping.

Technical requirements: TU 2211-136-05766801-2006

General Information				
Features	Good Thermal Stability			
	Homopolymer			
	Oxidation Resistant			
Uses	Engineering Parts			
	Packaging			
	Yarn			
Forms	Pellets			
Processing Method	Extrusion			
Physical	Nominal Value	Unit	Test Method	
Density	0.900	g/cm³		
Apparent Density	0.48 to 0.52	g/cm³		
Melt Mass-Flow Rate (MFR) (230°C/2.16				
kg)	1.5 to 2.0	g/10 min	ASTM D1238	
Ash Content	0.025 to 0.050	%		
Gel Content <sup>1</sup>				
> 200.0 µm	500			
0.700 to 1.50 mm	50.0	pcs/m²		
1.50 to 2.50 mm	3.00	pcs/m²		
> 2.50 mm	0.00	pcs/m²		
Thermal Creep Temperature <sup>2</sup>	90 to 96	°C		
Thermal-oxidative Deterioration (150°C)	15.0	day		
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	82 to 95			
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	34.0	MPa	ASTM D638	
Tensile Elongation (Yield)	10	%	ASTM D638	
Flexural Modulus	1500	MPa	ASTM D790	
Thermal	Nominal Value	Unit		
Vicat Softening Temperature <sup>3</sup>	150 to 154	°C		

NOTE	
1.	p.4.8 ?U 2211-136-05766801-2006
2.	at load 0.46 H/mm²
3.	in liquid medium under force 10 H

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

