# Vistalon™ 805

## Ethylene Propylene Copolymer Rubber

#### ExxonMobil Chemical

#### Message:

Vistalon 805 ethylene propylene rubber is a semi-crystalline ethylene and propylene copolymer with moderate Mooney viscosity, very high ethylene content and narrow molecular weight distribution. It can be used to modify plastics (such as for the production of TPO), or to produce highly filled loading pads, and raw materials are sold in the form of debris.

General Information			
Physical	Nominal Value	Unit	Test Method
Mooney Viscosity <sup>1</sup> (ML 1+4, 125°C)	33	MU	ASTM D1646
Ethylene Content	78.0	wt%	ASTM D3900
Legal statement			

有关详细的产品监管信息,请联系客户服务.未经埃克森美孚化工书面允许,这种产品包括其产品名称,不得在任何医疗应用领域予以使用或

NOTE

Radial cavity mold, polymer re-refined at 145±10°C

1. re-refined at 145±10°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

