NEFTEKHIM PP 4341S

Polypropylene Copolymer

Nizhnekamskneftekhim Inc.

Message:

Product obtained by copolymerization of propylene and ethylene in presence of complex metalorganic catalysts.

It incorporates increased long-term thermal stability, thermal-oxidative degradation resistance when PP is produced, processed and PP-made articles are exploited, effective nucleation, improved transparency, improved optical properties, improved antistatic properties to produce articles, improved rheology of melt.

Application: high quality food packing jet molding. Technical requirements: TU 2211-136-05766801-2006

General Information				
Additive	Antistatic			
	Nucleating Agent			
Features	Antistatic			
	Controlled Rheology			
	Copolymer			
	Good Thermal Stability			
	Nucleated			
	Opticals			
	Oxidation Resistant			
Uses	Food Packaging			
Forms	Pellets			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Density	0.900	g/cm³		
Apparent Density	0.48 to 0.60	g/cm³		
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	40 to 45	g/10 min	ASTM D1238	
Ash Content	0.025 to 0.050	%		
Thermal Creep Temperature ¹	70 to 80	°C		
Thermal-oxidative Deterioration (150°C)	15.0	day		
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	75 to 82			
Mechanical	Nominal Value	Unit	Test Method	
Flexural Modulus	950	МРа	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (23°C)	45	J/m	ASTM D256	
Thermal	Nominal Value	Unit		
Vicat Softening Temperature ²	130 to 138	°C		

NOTE	
1.	at load 0.46 H/mm²
2.	in liquid medium under force 10 H

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

