

Vinnolit® S 3265

Polyvinyl Chloride
Vinnolit GmbH & Co. KG

Message:

Vinnolit S 3265 is a porous suspension polymer with high bulk density. It is recommended for rigid profile, sheet and pipe extrusion.

General Information			
Uses	Piping		
	Profiles		
	Sheet		
Agency Ratings	EC 1907/2006 (REACH)		
Processing Method	Pipe Extrusion		
	Profile Extrusion		
	Sheet Extrusion		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.58	g/cm ³	ISO 60
K-Value	65.0		ISO 1628-2
Particle Size Distribution			ISO 4610
-- 1	< 5.0	%	
-- 2	> 98	%	
Volatile Matter	< 0.30	%	ISO 1269
NOTE			
1.	retained on 0.250 mm screen		
2.	retained on 0.063 mm screen		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT