# **DJSilicone NE-261**

#### Silicone

### DONGJUE SILICONE (NANJING) CO., LTD

### Message:

This product could be put to basic processing after adding vulcanizator DCBP. And it may not need second vulcanization when technical conditions properly controlled. It has excellent high and low temperature, electrical insulation, corona and arc resistance properties, which could be long-term used in temperature range from -60°C to 200°C. It is suitable for different kinds of electric wire cable, and parts for electrical insulator. Also this silicone rubber has excellent transparency, physical and mechanical properties, very suitable for cables, sealing strips and all kinds of transparent rubber tubes.

General Information				
Features	Arc Resistant			
	Electrically Insulating			
	High Clarity			
	High Heat Resistance			
	Low Temperature Resistant			
Uses	Electrical Parts			
	Seals			
	Tubing			
	Wire & Cable Applications			
Appearance	Translucent			
	White			
Physical	Nominal Value	Unit	Test Method	
Density	1.15 to 1.25	g/cm³	ASTM D1505	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness			ASTM D2240	
Shore A <sup>1</sup>	60 to 64			
Shore A <sup>2</sup>	58 to 62			
Elastomers	Nominal Value	Unit	Test Method	
Tensile Set			ASTM D412	
3	< 14	%		
4	< 12	%		
Tensile Strength <sup>5</sup> (Yield)	> 7.50	MPa	ASTM D412	
Tensile Elongation			ASTM D412	
Break <sup>6</sup>	> 300	%		
Break <sup>7</sup>	> 380	%		
Tear Strength	> 22.0	kN/m	ASTM D624	
Electrical	Nominal Value	Unit	Test Method	
Volume Resistivity	> 3.0E+14	ohms·cm	ASTM D257	

Dielectric Strength	> 20	kV/mm	ASTM D149
NOTE			
1.	For Tube		
2.	For Line		
3.	For Line		
4.	For Tube		
5.	For Line		
6.	For Tube		
7.	For Line		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

