

# PSM® HL-302

Thermoplastic

Wuhan Huali Environmental Technology Co., Ltd.

## Message:

PSM®HL-302 is a thermoplastic material. This product is available in the Asia-Pacific region. PSM®The main characteristics of the HL-302 are: environmental protection/green.

General Information			
Features	Biodegradable		
Physical	Nominal Value	Unit	Test Method
Density	1.30 - 1.40	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR)	25 - 35	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress	16.0 - 20.0	MPa	ISO 527-2
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	102 - 108	°C	ISO 306/B120

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

