

Keldax® 6798

Ethylene Copolymer
DuPont Packaging & Industrial Polymers

Message:

DuPont™ Keldax® 6798 is a low fog filled thermoplastic ethylene copolymer that provides acoustical sound barrier performance in automotive, construction, and industrial applications.

General Information	
Filler / Reinforcement	Filler
Features	Copolymer
	Low to No Fogging
	Sound Damping
Uses	Acoustic Barrier
	Automotive Applications
	Construction Applications
	Industrial Applications
Processing Method	Cast Film
	Extrusion Coating
	Laminating
	Sheet Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.90	g/cm ³	
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0	g/10 min	ASTM D1238, ISO 1133
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	80.0	°C	DSC
Additional Information	Nominal Value	Unit	
Maximum Processing Temperature	204	°C	
Extrusion	Nominal Value	Unit	
Cylinder Zone 1 Temp.	107	°C	
Cylinder Zone 2 Temp.	140	°C	
Cylinder Zone 3 Temp.	177	°C	
Cylinder Zone 4 Temp.	177	°C	
Cylinder Zone 5 Temp.	177	°C	
Adapter Temperature	177	°C	
Die Temperature	177	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

