

Shanghai Potomer SG6

Polyvinyl Chloride

Shanghai Potomer International Trade Co., Ltd.

Message:

PVC suspension Resin is Calcium Carbide base, mainly used as sheet, pipe, window profiles and other molded parts.

APPLICATIONS: rigid profiles, pipes, flexible profiles, plasticized hoses, cable insulation and sheathing, plasticized film and sheet

General Information		
Uses	Cable Jacketing	
	Film	
	Hose	
	Insulation	
	Piping	
	Profiles	
	Sheet	
Processing Method	Calendering	
	Extrusion	
Physical	Nominal Value	Unit
Apparent Density	> 0.48	g/cm ³
K (wear) Factor	63.0 to 65.0	
Sieve Analysis		
0.063mm sieve	> 90	%
0.25mm sieve	< 2.0	%
Viscosity	96.0 to 106	cm ³ /g
Volatile Matter	< 0.40	%
Fish Eye	< 20.0	pcs/400 cm ²
Impurities	< 16.0	pcs
Polymerization	850 to 950	
Whiteness - after 10min (160°C)	> 74	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

