

Kafrit PEX TA 2412 CL

Crosslinked Polyethylene

Kafrit NA Ltd.

Message:

TA 2412 CL catalyst masterbatch is used with Kafrit NA cross-linkable PEX-b compound TA 1108 HD to produce potable water tubing. TA 2412 CL contains white color pigment and a crosslinking catalyst which will complete the Sioplas System when extruded with PEX-b compounds such as TA 1108 HD. TA 2412 CL contains additives which protect the finished product from long term degradation caused by oxidation, heat, and exposure to chlorine and active metal ions. TA 2412 CL includes UV protection (HALS and UV absorber) for weathering exposure of the equivalent of 6 months in Arizona, as tested in accordance with ASTM F 2657.

General Information		
Additive	Antioxidant	
	Heat Stabilizer	
	Metal Deactivator	
	UV Stabilizer	
Features	Antioxidant	
	Good UV Resistance	
	Heat Stabilized	
	Non-Toxic	
Uses	Masterbatch	
	Piping	
	Potable Water Applications	
	Tubing	
Agency Ratings	NSF 61	
Appearance	Opaque	
	White	
Forms	Pellets	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Density	1.03	g/cm ³
Apparent Density	0.59	g/cm ³
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	11	g/10 min
Additional Information	Nominal Value	Unit
Volatiles	< 0.15	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

